

Title (en)

Distribution device for coating foodstuffs.

Title (de)

Verteilungsvorrichtung zum Beschichten von Nahrungsmitteln.

Title (fr)

Dispositif de distribution pour l'enrobage de produits alimentaires.

Publication

EP 0411174 B1 19940810 (EN)

Application

EP 89114154 A 19890801

Priority

EP 89114154 A 19890801

Abstract (en)

[origin: EP0411174A2] An apparatus for coating a foodstuff with particulate material comprising: a drum capable of rotating about a substantially horizontal longitudinal axis; a first conveyor adapted to travel through the drum; a second conveyor below the first conveyor, the second conveyor comprising at least first, second and third successive endless belts each having substantially horizontal upper run and a gap between each successive pair of belts, the second belt having an inclined portion extending to a position below the first belt, the gap between the second and third belts being situated within the drum; means for feeding particulate material onto the first conveyor; and means for feeding a foodstuff onto the first belt; such that in operation, particulate material is fed from the first conveyor onto the foodstuff on the first belt for coating the foodstuff on an upper side, the coated foodstuff is transported to the second belt with excess particulate material falling off the first belt onto the portion of the second belt below the first belt and is conveyed to the substantially horizontal upper run of the second belt to form a layer on which the coated foodstuff lies after being transported from the first belt to the substantially horizontal upper run of the second belt for coating the foodstuff on a bottom side, the coated foodstuff is fed to the third belt with further particulate material falling through the gap between the second and third belts onto an inside wall of the drum which rotates for conveying the further material to a position above the first conveyor upon which the further material falls by gravity, and the first conveyor transports the further material back to the second conveyor characterised in that there is provided a guiding device for distributing the further particulate material falling through the gap between the second and third belts onto the inside wall of the rum so that it forms a substantially even layer over the axial width of the inside wall of the drum.

IPC 1-7

A23P 1/08; B05C 19/06; B65G 45/26

IPC 8 full level

A23P 20/12 (2016.01); **B05C 19/06** (2006.01); **B65G 45/26** (2006.01)

CPC (source: EP US)

A23P 20/12 (2016.07 - EP US); **B05C 19/06** (2013.01 - EP US); **B65G 45/26** (2013.01 - EP US)

Cited by

EP2308327A1; US5798131A; EP0628254A1; EP1308099A3; EP1226763A1; NL1017214C2; WO2021101476A3; WO9515699A1; US7174846B2

Designated contracting state (EPC)

AT BE CH DE FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0411174 A2 19910206; EP 0411174 A3 19920603; EP 0411174 B1 19940810; AT E109627 T1 19940815; AU 5879590 A 19910207; AU 633937 B2 19930211; BR 9003747 A 19910903; CA 2021038 A1 19910202; CA 2021038 C 20001017; DE 68917468 D1 19940915; DE 68917468 T2 19950223; DK 171754 B1 19970512; DK 181290 A 19910202; DK 181290 D0 19900730; EG 19019 A 19941130; ES 2039132 A1 19930816; ES 2039132 B1 19940316; MX 174133 B 19940422; NO 175345 B 19940627; NO 175345 C 19941005; NO 903236 D0 19900719; NO 903236 L 19910204; PT 94861 A 19910418; PT 94861 B 19971128; US 5195454 A 19930323; US 5632369 A 19970527

DOCDB simple family (application)

EP 89114154 A 19890801; AT 89114154 T 19890801; AU 5879590 A 19900706; BR 9003747 A 19900731; CA 2021038 A 19900712; DE 68917468 T 19890801; DK 181290 A 19900730; EG 45390 A 19900801; ES 9001998 A 19900725; MX 2173190 A 19900725; NO 903236 A 19900719; PT 9486190 A 19900731; US 3089193 A 19930311; US 55665190 A 19900720