

Title (en)

AUTOMATIC CUT-OUT

Publication

EP 0412953 A3 19910502 (DE)

Application

EP 90890212 A 19900716

Priority

AT 190589 A 19890808

Abstract (en)

[origin: EP0412953A2] In an automatic cut-out, the switch link (5), the latch (6) and the latch abutment (7) are combined to form an assembly which can be pivoted about a bearing journal (4) provided in the housing (1). The latch (6) is stressed by a spring (8) and can be pivoted with respect to the latch abutment (7) which, for its part, is supported such that it can pivot on the switch link (5). This assembly is coupled by a thrust guide (25), which engages in a mouth (9) between the latch (6) and the latch abutment (7), to an operating head (20). As a result of pivoting the latch (6) under the influence of the plunger (54) of the magnetic trip device (51) or of the tension lever (67) under the influence of the bimetallic strip (41), the mouth (9) is opened such that the end (26), which is held in it, of the thrust guide (25) is released. In consequence, the switch link (5) can be pivoted by the tension spring (16) into the off position. The bimetallic strip (41) is mounted on a support (42) which is fixed in the housing (1) via conical journals (45) which engage in holes (44) in the support (42). In the off position, the switch link (5) rests on the support (42) for the bimetallic strip (41). <IMAGE>

IPC 1-7

H01H 71/52

IPC 8 full level

H01H 71/52 (2006.01); **H01H 71/04** (2006.01); **H01H 71/10** (2006.01); **H01H 71/24** (2006.01)

CPC (source: EP)

H01H 71/526 (2013.01); **H01H 71/04** (2013.01); **H01H 71/1027** (2013.01); **H01H 71/2409** (2013.01); **H01H 71/2454** (2013.01);
H01H 71/2463 (2013.01); **H01H 2300/046** (2013.01)

Citation (search report)

- [AP] EP 0338930 A1 19891025 - HAGER ELECTRO [FR]
- [AD] DE 3520905 A1 19851219 - MITSUBISHI ELECTRIC CORP [JP]

Cited by

US7135953B2; CZ300092B6; EP0897186A3; EP0577586A1; DE10126851C1; EP1146534A1; EP0570647A1; EP0564380A1; FR2689309A1;
EP0506503A1; FR2674679A1; TR27123A; CN108172479A; US6816055B2; EP1884975B1; WO03012812A1; WO9630924A1

Designated contracting state (EPC)

AT CH DE ES FR GB IT LI

DOCDB simple family (publication)

EP 0412953 A2 19910213; EP 0412953 A3 19910502; EP 0412953 B1 19940831; AT E110882 T1 19940915; AU 6022690 A 19910214;
AU 627054 B2 19920813; DE 59006962 D1 19941006; ES 2063331 T3 19950101; HK 60396 A 19960419; HU 205483 B 19920428;
HU 904706 D0 19910128; HU T56659 A 19910930; TN SN90113 A1 19910305; TR 24652 A 19920101

DOCDB simple family (application)

EP 90890212 A 19900716; AT 90890212 T 19900716; AU 6022690 A 19900807; DE 59006962 T 19900716; ES 90890212 T 19900716;
HK 60396 A 19960411; HU 470690 A 19900801; TN SN90113 A 19900808; TR 71090 A 19900808