

Title (en)  
DEVICE FOR ACTIVATING THE BOLD OF A LOCK

Publication  
**EP 0413964 B1 19921223 (DE)**

Application  
**EP 90113830 A 19900719**

Priority  
DE 8910095 U 19890823

Abstract (en)  
[origin: EP0413964A1] An actuating device preferably consisting of only two parts, namely a rotary member (1) and a device housing (2), can, because of the cross-sectional shape of its device housing (2), be installed in a lock, door, window or the like instead of a conventional lock cylinder of the same housing cross-section, so that the bolt of this lock can be transferred from the release position into the effective locking position, and vice versa, by means of the locking bit (13) of the actuating device. A 90 DEG -rotation of the rotary member (1) in the device housing (2) is sufficient for a complete stroke of the lock bolt. During assembly, the rotary member (1) assumes a rotary position in which, in the same way as with a lock cylinder, the locking bit (13) does not project laterally beyond the contour of the device housing (2). In a rotary position different from this, namely the working rotary position of the rotary member (1), and of course also on the way to this, the locking bit projects beyond the contour of the device housing (2). <IMAGE>

IPC 1-7  
**E05B 17/04**

IPC 8 full level  
**E05B 17/04** (2006.01); **E05B 63/00** (2006.01)

CPC (source: EP)  
**E05B 17/047** (2013.01); **E05B 63/0065** (2013.01); **E05B 63/0034** (2013.01)

Cited by  
FR2824863A1; EP2336460A1; IT202200006050A1; AU2006223992B2; EP2436858B1

Designated contracting state (EPC)  
AT DE FR GB IT

DOCDB simple family (publication)  
**EP 0413964 A1 19910227**; **EP 0413964 B1 19921223**; AT E83826 T1 19930115; DE 59000653 D1 19930204; DE 8910095 U1 19891005

DOCDB simple family (application)  
**EP 90113830 A 19900719**; AT 90113830 T 19900719; DE 59000653 T 19900719; DE 8910095 U 19890823