

Title (en)
Printer initialization system

Title (de)
Drucker-Initialisierungssystem

Title (fr)
Système d'initialisation d'imprimante

Publication
EP 0415861 B1 19960117 (EN)

Application
EP 90480071 A 19900515

Priority
US 39887289 A 19890825

Abstract (en)
[origin: EP0415861A2] A printer control system which enables the using application program to automatically selectively alter printer default parameters, to automatically selectively delete previously downloaded fonts and macros, and to enable the printer to operate from one of several datastream formats. The system allows the printer to initialize default parameters for a succeeding job during the printing of a current job as long as the datastream format is unchanged, and allows the deletion of downloaded fonts as long as they are not needed for the current or future pages being printed for the current job.

IPC 1-7
G06K 15/00; **G06K 15/02**

IPC 8 full level
G06F 3/12 (2006.01); **G06F 9/06** (2006.01); **G06K 15/00** (2006.01); **G06K 15/02** (2006.01)

CPC (source: EP US)
G06K 15/00 (2013.01 - EP US); **G06K 15/02** (2013.01 - EP US); **G06K 2215/0008** (2013.01 - EP US); **G06K 2215/0011** (2013.01 - EP US)

Cited by
EP0576305A1; EP0534723A3; US5696891A; EP0571168A1; US5671341A; US8305602B2; EP0571169B1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0415861 A2 19910306; **EP 0415861 A3 19920527**; **EP 0415861 B1 19960117**; DE 69024881 D1 19960229; DE 69024881 T2 19960808; JP H0385627 A 19910410; JP H0580012 B2 19931105; US 5050098 A 19910917

DOCDB simple family (application)
EP 90480071 A 19900515; DE 69024881 T 19900515; JP 19604290 A 19900724; US 39887289 A 19890825