

Title (en)
METHOD OF REMOVING SOOT FROM LUBRICATING OILS

Publication
EP 0416907 A3 19910410 (EN)

Application
EP 90309735 A 19900905

Priority
US 40403289 A 19890907

Abstract (en)
[origin: EP0416907A2] Soot can be effectively removed from a lubricating oil used in a non-gasoline fueled internal combustion engine by contacting the oil with a heterogenous strong base. This results in improved engine cleanliness and reduced engine wear.

IPC 1-7
C10M 175/00; **C10M 177/00**

IPC 8 full level
C10M 125/10 (2006.01); **C10M 175/00** (2006.01); **C10M 175/02** (2006.01); **C10M 177/00** (2006.01); **C10N 10/02** (2006.01); **C10N 10/04** (2006.01); **C10N 40/25** (2006.01); **F02B 77/04** (2006.01)

CPC (source: EP KR)
C10M 125/00 (2013.01 - KR); **C10M 175/0091** (2013.01 - EP); **C10M 177/00** (2013.01 - EP); **F02B 77/04** (2013.01 - EP)

Citation (search report)

- [X] GB 929177 A 19630619 - KIICHIRO SARUI
- [X] US 1914999 A 19330620 - MAVERICK GEORGE M, et al
- [X] GB 476422 A 19371206 - JOHN KAY RUSSELL, et al
- [XD] EP 0275148 A2 19880720 - EXXON CHEMICAL PATENTS INC [US]
- [XP] EP 0371639 A1 19900606 - EXXON RESEARCH ENGINEERING CO [US]

Cited by
US7534747B2; US7250126B2; US8016125B2; US7744660B2; US7384896B2; WO9620262A1; WO2005003266A1; US8607991B2; US8691096B2; US7913858B2; US7417012B2; US8076273B2; US8299000B2

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI NL SE

DOCDB simple family (publication)
EP 0416907 A2 19910313; **EP 0416907 A3 19910410**; AU 6218890 A 19910314; AU 638274 B2 19930624; BR 9004414 A 19910910; CA 2024005 A1 19910308; JP H03152196 A 19910628; KR 910006467 A 19910429

DOCDB simple family (application)
EP 90309735 A 19900905; AU 6218890 A 19900906; BR 9004414 A 19900905; CA 2024005 A 19900824; JP 23883590 A 19900907; KR 900014045 A 19900906