

Title (en)
METHOD OF MAKING MASTIC ASPHALT SURFACINGS

Publication
EP 0418809 B1 19930707 (DE)

Application
EP 90117923 A 19900918

Priority
DE 3931239 A 19890919

Abstract (en)
[origin: EP0418809A1] Preheated colour shreds from melt-coloured plastics films are applied to the freshly prepared and still hot surface of a mastic asphalt with a surface coverage of up to 95 %. The regions of the mastic asphalt remaining between the colour shreds are sanded. If appropriate, a sealing or smoothing surface layer is applied on top.

IPC 1-7
E01C 7/18; E01C 7/32; E01C 7/35; E01C 13/00; E04D 7/00; E04F 15/12

IPC 8 full level
E01C 7/18 (2006.01); **E01C 7/32** (2006.01); **E01C 7/35** (2006.01); **E01C 13/00** (2006.01); **E01C 13/06** (2006.01); **E04D 7/00** (2006.01); **E04F 15/12** (2006.01)

CPC (source: EP)
E01C 7/182 (2013.01); **E01C 7/32** (2013.01); **E01C 7/353** (2013.01); **E01C 13/065** (2013.01); **E04D 7/005** (2013.01); **E04F 15/12** (2013.01)

Cited by
EP0995858A3; US9498931B2

Designated contracting state (EPC)
AT BE CH DE DK FR GB LI LU NL SE

DOCDB simple family (publication)
EP 0418809 A1 19910327; EP 0418809 B1 19930707; AT E91308 T1 19930715; DE 3931239 C1 19910131; DE 59001910 D1 19930812

DOCDB simple family (application)
EP 90117923 A 19900918; AT 90117923 T 19900918; DE 3931239 A 19890919; DE 59001910 T 19900918