

Title (en)

COMBUSTION METHOD FOR GRANULAR SYNTHETIC RESIN WASTE, PARTICULARLY FROM ION EXCHANGERS

Publication

EP 0419992 A3 19920102 (DE)

Application

EP 90117860 A 19900917

Priority

DE 3931900 A 19890925

Abstract (en)

[origin: EP0419992A2] For the combustion of loose synthetic resin material, in particular ion exchanger resins, dry resins mixed with granulated alumina or moist masses are blown together with air for combustion with air supply into the lower region of a fluidised bed with excess granulated alumina which, in particular, has a particle size of ≤ 1 mm, especially 100-400 μ m, and preferably is present in the furnace in a quantity more than 5 times that of the resin. Cation exchangers are burnt with an oxygen excess, especially with a total lambda value of ≥ 2 , whereas in the case of anion exchanger resins, less than stoichiometric quantities of oxygen are provided in the lower zone, especially with lambda values of between 0.5 and 0.8. Advantageously, the fluidised bed is designed as a two-zone fluidised bed with a lower stationary fluidised bed (especially a rotating bed) and an upper circulating bed. Temperatures of 900 DEG C are advantageous. Especially, additives such as, for example, lime for the absorption of sulphur oxide are blown into the upper region. <IMAGE>

IPC 1-7

F23G 5/30; **F23G 7/12**

IPC 8 full level

F23G 5/30 (2006.01); **F23G 7/12** (2006.01)

CPC (source: EP)

F23G 5/30 (2013.01); **F23G 7/12** (2013.01); **F23G 2202/101** (2013.01); **F23G 2203/501** (2013.01); **F23G 2203/502** (2013.01); **F23G 2203/503** (2013.01)

Citation (search report)

- [A] WO 8102772 A1 19811001 - ENERGY INC [US]
- [AD] DE 3702089 C1 19880630 - KERNFORSCHUNGSANLAGE JUELICH [DE]
- [AP] US 4938156 A 19900703 - YAHATA TANEAKI [JP]

Cited by

US5806444A; US5551358A; WO9523317A1; WO9417332A3

Designated contracting state (EPC)

AT BE CH DE LI NL SE

DOCDB simple family (publication)

EP 0419992 A2 19910403; **EP 0419992 A3 19920102**; DE 3931900 A1 19910404

DOCDB simple family (application)

EP 90117860 A 19900917; DE 3931900 A 19890925