

Title (en)

Boiling type cooler device for power semiconductor switching elements.

Title (de)

Kühlungsanordnung vom Kochertyp für Leistung-Halbleiterschaltungselemente.

Title (fr)

Dispositif de refroidissement du type à ébullition pour des éléments semi-conducteurs commutateurs de puissance.

Publication

**EP 0420668 A2 19910403 (EN)**

Application

**EP 90310641 A 19900928**

Priority

- JP 3667690 A 19900216
- JP 20682690 A 19900806
- JP 25207589 A 19890929

Abstract (en)

A boiling cooler device for cooling thyristors, etc., is made of copper and utilizes water or an aqueous solution of ethylene glycol as the cooling medium. The cooler fins 31 constituting the evaporators of the device are disposed to a side of a common liquid reservoir 33 directly coupled to the condensor 24, to be communicated thereto via substantially horizontally extending ducts 32 (Figs. 8 and 9). Each cooler fin 31 may be coupled to the common reservoir 33 via two parallel ducts 34 and 35 (Fig. 10). The cooler fins 31 may each comprise vertically extending interior conduits 42 at the interior side of the heat absorbing surfaces 31a (Figs. 13 through 15). The evaporator 51 may comprise a first cooling medium conduit 53 and second cooling medium conduits 54 having a smaller overall cross sectional area than the first conduit 53 (Figs. 32 and 33). Metal particles 61, preferably having a particle size of from about 400 to 1000 micrometers, may be attached to the heat transfer surfaces of the cooler fins 31 (Figs. 41 and 42). Further, optimal ranges of a dimensionless number F for stabilizing the cooling efficiency is disclosed for respective cooling media.

IPC 1-7

**H01L 23/427**

IPC 8 full level

**F28D 15/02** (2006.01); **F28F 13/18** (2006.01); **H01L 23/427** (2006.01)

CPC (source: EP KR)

**F25D 3/00** (2013.01 - KR); **F28D 15/0266** (2013.01 - EP); **F28F 13/187** (2013.01 - EP); **F28F 21/085** (2013.01 - EP); **H01L 23/427** (2013.01 - EP); **H01L 2924/0002** (2013.01 - EP)

Cited by

CN102545240A; CN110701934A; CN102570480A

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

**EP 0420668 A2 19910403**; **EP 0420668 A3 19911002**; AU 618203 B2 19911212; AU 631506 B2 19921126; AU 632431 B2 19921224; AU 6324890 A 19910606; AU 634097 B2 19930211; AU 8550691 A 19911205; AU 8550791 A 19911205; AU 8564391 A 19911205; CN 1056350 A 19911120; KR 910006678 A 19910429

DOCDB simple family (application)

**EP 90310641 A 19900928**; AU 6324890 A 19900926; AU 8550691 A 19911001; AU 8550791 A 19911001; AU 8564391 A 19911004; CN 90109366 A 19900929; KR 900015645 A 19900929