

Title (en)
THREAD-CUTTING DEVICE FOR SEWING MACHINES

Publication
EP 0420856 B1 19921202 (DE)

Application
EP 89905094 A 19890426

Priority
DE 3819135 A 19880606

Abstract (en)
[origin: WO8912129A1] In a prior art sewing machine, the tensioner is released in both directions of the axially mobile gear element (21), and hence the thread tensioner is also opened when the needle thread is seized. In the new design, the motion of the gear element (21) is transmitted via a one-way coupling (53), and therefore the thread tensioner is open only while the needle thread is being tensioned.

IPC 1-7
D05B 47/00; D05B 65/00

IPC 8 full level
D05B 47/00 (2006.01); D05B 47/02 (2006.01); D05B 65/00 (2006.01); D05B 65/02 (2006.01)

CPC (source: EP KR US)
D05B 47/00 (2013.01 - EP KR US); D05B 65/00 (2013.01 - EP US)

Designated contracting state (EPC)
CH IT LI NL

DOCDB simple family (publication)
DE 3819135 C1 19890713; BR 8907056 A 19910102; EP 0420856 A1 19910410; EP 0420856 B1 19921202; ES 2013511 A6 19900501; JP H03504809 A 19911024; JP H0528640 B2 19930426; KR 900700679 A 19900816; KR 960015663 B1 19961120; US 5113774 A 19920519; WO 8912129 A1 19891214

DOCDB simple family (application)
DE 3819135 A 19880606; BR 8907056 A 19890426; EP 8900452 W 19890426; EP 89905094 A 19890426; ES 8901949 A 19890605; JP 50450589 A 19890426; KR 890702434 A 19891223; US 49926590 A 19900531