

Title (en)
Exhaust valve alloy.

Title (de)
Auspuffventillegierung.

Title (fr)
Alliage pour soupape d'échappement.

Publication
EP 0421705 A1 19910410 (EN)

Application
EP 90310724 A 19901001

Priority
GB 8922161 A 19891002

Abstract (en)
An alloy for a marine diesel exhaust valve comprising 0.02-0.07% C, 24-32% (preferably 24-28%) Cr, 0.7-3% Ti, 0.7-1.5% Al, 0.7-1.5% Hb, 0-1% Zr, 0-0.006% B, 0-1% Fe, balance essentially nickel, and exhaust valves made from this alloy.

IPC 1-7
C22C 19/05

IPC 8 full level
C22C 19/05 (2006.01); **F02B 3/06** (2006.01)

CPC (source: EP)
C22C 19/058 (2013.01); **F02B 3/06** (2013.01)

Citation (search report)
• [AD] DE 3511860 A1 19851010 - DAIDO STEEL CO LTD [JP], et al
• [AD] EP 0109350 A2 19840523 - MITSUBISHI HEAVY IND LTD [JP], et al
• [A] US 2570194 A 19511009 - GEORGE BIEBER CLARENCE, et al
• [A] FR 1584027 A 19691212
• [A] PATENT ABSTRACTS OF JAPAN, vol. 1, no. 200 (C-298)[1923], 16th August 1985; & JP-A-60 70 155 (HITACHI KINZOKU K.K.) 20-04-1985

Cited by
EP0857793A1; DE102007062417B4; DE102007062417A1; WO02092865A1; WO2009079972A1

Designated contracting state (EPC)
AT BE CH DE GB IT LI NL SE

DOCDB simple family (publication)
EP 0421705 A1 19910410; CA 2026551 A1 19910403; GB 8922161 D0 19891115; JP H03120328 A 19910522

DOCDB simple family (application)
EP 90310724 A 19901001; CA 2026551 A 19900928; GB 8922161 A 19891002; JP 26036490 A 19900928