

Title (en)
ELECTROMAGNETIC RELAY

Publication
EP 0423834 A3 19911227 (EN)

Application
EP 90120252 A 19901022

Priority
• JP 13355689 U 19891116
• JP 13514289 U 19891121
• JP 13574189 U 19891122
• JP 27460189 A 19891020
• JP 27460289 A 19891020
• JP 29597589 A 19891114

Abstract (en)
[origin: EP0423834A2] The electromagnetic relay of the present invention ensures smooth operating characteristic as a relay for an elongated lifetime, because the movable iron piece turns on the same plane as the movable contact piece. Moreover, the operating characteristic can be adjusted from the lateral side even after assembling work and even with the inner components kept mounted. This is because a front end of the fixed contact terminal is projected sideways from the lateral face of the base, and the receiver part of the common terminal is bent outwards. In the electromagnetic relay of the present invention, the movable contact piece block is united with the movable iron piece through a secondary insertion-molding, and the base is fixed to the electromagnet block by using a solvent, thereby requiring no positioning accuracy of components.

IPC 1-7
H01H 51/22; H01H 50/54

IPC 8 full level
H01H 51/22 (2006.01)

CPC (source: EP)
H01H 51/229 (2013.01)

Citation (search report)
• [Y] DE 3303665 A1 19840809 - SIEMENS AG [DE]
• [Y] DE 1867987 U 19630228 - HALLER & CO E [DE]
• [A] DE 3311308 C1 19841025 - SIEMENS AG
• [A] EP 0313385 A2 19890426 - NEC CORP [JP]
• [A] US 3624571 A 19711130 - MAGIDA NATHAN H

Cited by
DE19705508C1; DE19635275C1; US5617066A; DE4408980B4; DE19625848A1; EP2645399A4; EP3128530A1; US9093239B2; WO9742643A1; WO9422156A1; WO9809311A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IT LI NL SE

DOCDB simple family (publication)
EP 0423834 A2 19910424; EP 0423834 A3 19911227

DOCDB simple family (application)
EP 90120252 A 19901022