

Title (en)  
FLUSHING PIPE FOR A TOILET

Publication  
**EP 0424313 A3 19911016 (DE)**

Application  
**EP 90810769 A 19901005**

Priority  
CH 377889 A 19891017

Abstract (en)  
[origin: EP0424313A2] The flushing pipe is to be connected at the top to a flushing cistern and at the bottom to a toilet bowl. If the flushing pipe is used for suction-removal of odours, a closing part (7) is cut out in one of the two connection pieces (3) along a wall region (7a) of reduced wall thickness. A suction-removal pipe is welded onto this connection piece (3) or connected by a coupling sleeve. The flushing pipe can also be used for a toilet without suction-removal of odours. <IMAGE>

IPC 1-7  
**E03D 9/052**

IPC 8 full level  
**E03D 9/052** (2006.01)

CPC (source: EP)  
**E03D 9/052** (2013.01)

Citation (search report)

- [YD] CH 368439 A 19630331 - GEBERT & CIE [CH]
- [Y] DE 2612240 A1 19761014 - KAY FRANCIS XAVIER
- [A] DE 922040 C 19550107 - BURKHART HANS, et al

Designated contracting state (EPC)  
AT BE CH DE DK ES FR GB IT LI NL

DOCDB simple family (publication)  
**EP 0424313 A2 19910424; EP 0424313 A3 19911016; EP 0424313 B1 19930714**; AT E91522 T1 19930715; CA 2026380 A1 19910418; DE 59001961 D1 19930819; PT 95539 A 19910814

DOCDB simple family (application)  
**EP 90810769 A 19901005**; AT 90810769 T 19901005; CA 2026380 A 19900927; DE 59001961 T 19901005; PT 9553990 A 19901008