

Title (en)
RANGE FINDING DEVICE

Publication
EP 0424409 A4 19920115 (EN)

Application
EP 89907048 A 19890620

Priority
AU PI887688 A 19880620

Abstract (en)
[origin: WO8912837A1] A pulse generator (11) provides timed trigger signals to an image intensifier driver (12) which drives the gate of the image intensifier (9). The pulse generator also triggers the drive circuitry and diode array (7) to emit light towards a scene. Reflected light from the scene enters the imaging system through filter (7) and lens (8) focusing the filtered light onto the intensifier (9) which is observed by video camera (10). The output of video camera (10) is connected to a frame store (14) and sync processor (13). The system controller (15) regulates switch (16) which allows the diode array to be operated in pulsed mode (a), continuous mode (b) and off mode (c). The three outputs of frame store (14) are processed by circuitry (18) to produce data representing range information about the scene. This information after passing through analog convertor (19) is combined with video sync information from the sync processor (13) and the resulting signal displayed on video monitor (21).

IPC 1-7
G01S 17/08; **G01C 3/08**

IPC 8 full level
G01C 3/06 (2006.01); **G01S 17/08** (2006.01); **G01S 17/89** (2020.01); **H04N 5/232** (2006.01)

CPC (source: EP US)
G01S 17/08 (2013.01 - EP US); **G01S 17/89** (2013.01 - EP US)

Citation (search report)

- [A] US 4298280 A 19811103 - HARNEY ROBERT C
- [A] US 4678323 A 19870707 - SATO YUICHI [JP], et al
- [A] US 4501961 A 19850226 - STAUFFER NORMAN L [US]
- See references of WO 8912837A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
WO 8912837 A1 19891228; EP 0424409 A1 19910502; EP 0424409 A4 19920115; JP H03505123 A 19911107

DOCDB simple family (application)
AU 8900263 W 19890620; EP 89907048 A 19890620; JP 50662589 A 19890620