

Title (en)  
INTERLOCKING BLOCKS

Publication  
**EP 0424592 B1 19930922 (DE)**

Application  
**EP 89810800 A 19891024**

Priority  
EP 89810800 A 19891024

Abstract (en)  
[origin: EP0424592A1] The interlocking blocks possess, on at least two opposite sides (2, 3), outwardly tapering teeth (4, 5). On the front sides (9) of one side (3), the teeth (5) are provided with tothing tongues (10) and on the front sides (6) of the other side (2), the teeth (4) are provided with tothing grooves (8). In addition, the toothed flanks (11, 12) of one tooth row (5) possess distance projections (13). An interlocking block can be constructed, for example, as a rectangular block (1) and possess, on its longitudinal sides (2, 3), in each case three teeth (4, 5) and, on its narrow sides (14, 15), either a tongue (16) or a groove (17). <??>The interlocking blocks can be used either for constructing cycle paths with few unevennesses, the teeth locking into one another, or they can be used as lawn interlocking blocks, the teeth in each case abutting against one another and being locked by the tothing tongues (10) and tothing grooves (8). <IMAGE>

IPC 1-7  
**E01C 5/00**

IPC 8 full level  
**E01C 5/00** (2006.01); **E01C 9/00** (2006.01)

CPC (source: EP US)  
**E01C 5/00** (2013.01 - EP US); **E01C 9/004** (2013.01 - EP US); **E01C 2201/02** (2013.01 - EP US)

Cited by  
AT401075B; EP0530428A1; EP2472017A3; US9840813B2; US10081918B2; US9677228B2; US10240301B2; US9752288B2; US10087585B2; US10337152B2; US8609215B2; US8888401B2; US9428906B2; US9745742B2

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0424592 A1 19910502; EP 0424592 B1 19930922**; AT E94927 T1 19931015; CA 2028357 A1 19920424; CA 2028357 C 19991207; DE 58905708 D1 19931028; US 5133620 A 19920728

DOCDB simple family (application)  
**EP 89810800 A 19891024**; AT 89810800 T 19891024; CA 2028357 A 19901023; DE 58905708 T 19891024; US 60265190 A 19901024