

Title (en)  
REGULATING MECHANISM FOR A PARTITIONED DOCTOR BLADE

Publication  
**EP 0425432 A3 19910807 (DE)**

Application  
**EP 90810771 A 19901009**

Priority  
CH 381589 A 19891023

Abstract (en)  
[origin: JPH03153355A] PURPOSE: To save on time and papers when an adjustment work is repeated by providing each of sectional bolts with a counter for counting the number of executed revolutions of each of the sectional bolts to be rotated in order to adjust each of adjustment bolts. CONSTITUTION: A doctor 1 forms part of an ink groove in a printing press together with a fountain roller 2 and a horizontal beam 3, and each of measurement counters 8 is fitted into each of the end parts of slender shaft parts 63. Prior to transmitting an ink, adjustment bolts 6 are screwed in to set the measurement counter 8. After that, all the counters 8 are adjusted to individually desired values in the sections. These values differing in compliance with printing models are registered and are collected per printing model. When printing the identical models in succession, the counters 8 are adjusted to at least, the almost right values immediately.

IPC 1-7  
**B41F 31/04**

IPC 8 full level  
**B41F 31/04** (2006.01)

CPC (source: EP US)  
**B41F 31/04** (2013.01 - EP US); **Y10S 101/47** (2013.01 - EP US)

Citation (search report)  
• [X] US 2607315 A 19520819 - LEEDY HERBERT R, et al  
• [YD] DE 2435321 A1 19760212 - PITER ROLAND  
• [Y] US 3559573 A 19710202 - HANTSCHO GEORGE E  
• [A] US 4372207 A 19830208 - TOYODA HIDEAKI [JP]  
• [A] GB 2079676 A 19820127 - MILLER JOHANNISBERG DRUCKMASCH

Cited by  
US6112661A; EP1260365A1; DE4242744A1; DE4242744C2; EP3569416A1; WO2004113077A1; US6681698B2

Designated contracting state (EPC)  
CH DE FR GB IT LI SE

DOCDB simple family (publication)  
**EP 0425432 A2 19910502; EP 0425432 A3 19910807; EP 0425432 B1 19940629**; CH 679919 A5 19920515; DE 59006304 D1 19940804; JP H03153355 A 19910701; US 5052297 A 19911001

DOCDB simple family (application)  
**EP 90810771 A 19901009**; CH 381589 A 19891023; DE 59006304 T 19901009; JP 28571290 A 19901023; US 60214890 A 19901023