

Title (en)
Ceiling recess cage.

Title (de)
In der Decke integrierte Gehäuse.

Title (fr)
Cage en retrait dans un plafond.

Publication
EP 0427498 A2 19910515 (EN)

Application
EP 90312106 A 19901105

Priority
GB 8925503 A 19891110

Abstract (en)
A spacer device is provided for use with a recessed light fitting to ensure a minimum spacing between the light fitting and any structural member located above or behind a panel mounting the light fitting. The device consists of a frame-like structure with two or more members (1, 2) which are movable relative to each other, e.g. by pivoting, to allow the device to be adjusted between a collapsed condition in which it can be introduced through the hole in the panel to an expanded condition. A spring can be included to ensure automatic expansion and the device can engage the hole to ensure correct positioning relative thereto.

IPC 1-7
F21V 21/04

IPC 8 full level
F21V 21/04 (2006.01)

CPC (source: EP)
F21V 21/04 (2013.01); **F21V 25/00** (2013.01); **F21S 8/026** (2013.01); **F21V 15/02** (2013.01)

Cited by
DE102013112303A1; DE202014105845U1; EP2541125A1; EP2546564A1; DE19755996C2; EP2787274A1; FR3004236A1; EP2860445A1; EP2620701A1; FR2986055A1; FR3081042A1; DE102014101337A1; DE102014101337B4; AT515009A3; AT515009B1; WO2012080758A3; DE102013112303B4; EP3029212A2; EP2592335B1

Designated contracting state (EPC)
BE CH DE FR GB IT LI NL

DOCDB simple family (publication)
EP 0427498 A2 19910515; EP 0427498 A3 19911106; EP 0427498 B1 19950517; DE 69019468 D1 19950622; DE 69019468 T2 19960104; GB 2237867 A 19910515; GB 2237867 B 19920902; GB 8925503 D0 19891228

DOCDB simple family (application)
EP 90312106 A 19901105; DE 69019468 T 19901105; GB 8925503 A 19891110