

Title (en)
FOOTSUPPORT ON AN INSTALLATION BLOCK

Publication
EP 0427678 B1 19930526 (DE)

Application
EP 90810846 A 19901105

Priority
CH 405789 A 19891110

Abstract (en)
[origin: US5150480A] The foot support (5) has an H-shaped beam (6) as well as two feet (7). The beam (6) and the feet (7) are made from metal pipes with rectangular cross section. The height of the foot support (5) is adjusted by adjusting the depth of insertion of the feet (7) into the beam (6). The feet (7) and the beam (6) have bent parts (7a and 6c) for fastening. The foot support (5) is also suitable for in-front-of-the-wall mounting and the in-the-wall mounting of the installation block. The feet (7) are inserted into the beam (6) such that its bent parts (7a) are directed toward the building wall (1) in the first case and away from the wall in the second case. The foot support (5) has a high load-bearing capacity and is particularly suitable for the installation of a wall-mounted toilet in front of a light-construction wall.

IPC 1-7
E03C 1/01

IPC 8 full level
E03C 1/01 (2006.01); **E03D 11/14** (2006.01)

CPC (source: EP US)
E03D 11/146 (2013.01 - EP US); **Y10T 403/32491** (2015.01 - EP US); **Y10T 403/7041** (2015.01 - EP US)

Citation (examination)
DE 8234025 U1 19830324

Designated contracting state (EPC)
AT BE CH DE DK FR IT LI NL

DOCDB simple family (publication)
US 5150480 A 19920929; AT E89883 T1 19930615; DE 59001553 D1 19930701; DE 9014603 U1 19910103; DK 0427678 T3 19930621; EP 0427678 A1 19910515; EP 0427678 B1 19930526

DOCDB simple family (application)
US 60688390 A 19901031; AT 90810846 T 19901105; DE 59001553 T 19901105; DE 9014603 U 19901022; DK 90810846 T 19901105; EP 90810846 A 19901105