

Title (en)

Method for producing substrate for PS plate.

Title (de)

Herstellungsverfahren für ein vorsensibilisiertes Flachdruckplattensubstrat.

Title (fr)

Méthode pour la fabrication d'un substrat pour plaque présensibilisée d'impression.

Publication

EP 0428071 B1 19950215 (EN)

Application

EP 90121414 A 19901108

Priority

- JP 752590 A 19900117
- JP 29442189 A 19891113

Abstract (en)

[origin: EP0428071A2] A method for producing a substrate for a presensitized plate for use in making a lithographic printing plate comprises surface-roughening and anodizing an aluminum plate, wherein the surface-roughened and anodized aluminum plate is then, in order, subjected to the following treatments: (a) a dyeing treatment with a dye; (b) a sealing treatment; and (c) an optional hydrophilization treatment. The method can provide an excellent aluminum substrate for presensitized plates which are excellent in half tone dot reproduction, resistance to background contamination, ability of recovering from contamination with ink and easy achievement of good balance between water and ink and which can correspondingly provide lithographic printing plate having high printing durability.

IPC 1-7

B41N 3/03

IPC 8 full level

B41N 3/00 (2006.01); **B41N 3/03** (2006.01)

CPC (source: EP)

B41N 3/034 (2013.01)

Citation (examination)

WORLD PATENTS INDEX LATEST Section PQ, Week 8310, Derwent Publications Ltd., London, GB; JP-A-58 014 797 (FUJI PHOTO FILM KK)

Cited by

US6715420B2; WO03004281A1

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

EP 0428071 A2 19910522; EP 0428071 A3 19911211; EP 0428071 B1 19950215; DE 69016931 D1 19950323; DE 69016931 T2 19950614; JP H03215098 A 19910920

DOCDB simple family (application)

EP 90121414 A 19901108; DE 69016931 T 19901108; JP 752590 A 19900117