

Title (en)

DRIVING DEVICE FOR INDEPENDENTLY ROTATING WHEELS OF A RAILWAY VEHICLE WITH DRIVING SHAFT

Publication

EP 0428091 B1 19930908 (FR)

Application

EP 90121582 A 19901112

Priority

FR 8914915 A 19891114

Abstract (en)

[origin: EP0428091A1] Device for driving independent wheels (12, 13) of a rail vehicle having a driving axle (20) in rotation from a motor (14), a reducer (15) and a mechanical differential (18). The mechanical differential (18) is arranged outside one of the wheels (12), of which one of the output pinions is coupled directly to the nearest wheel and the other is coupled to the other wheel (13) by means of a connecting shaft (20).<IMAGE>

IPC 1-7

B61C 9/44; B61C 9/52

IPC 8 full level

B61C 9/44 (2006.01); **B61C 9/52** (2006.01)

CPC (source: EP)

B61C 9/44 (2013.01); **B61C 9/52** (2013.01)

Cited by

EP2960132A1; WO2015198162A1; CN109415070A; CN103381839A; CN106343927A; EP0911239A1; FR2770190A1; US11233440B2; WO2018002210A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0428091 A1 19910522; EP 0428091 B1 19930908; AT E94129 T1 19930915; DE 69003223 D1 19931014; DE 69003223 T2 19940105; DK 0428091 T3 19940131; ES 2044374 T3 19940101; FR 2654402 A1 19910517; FR 2654402 B1 19920110; PT 95880 A 19920731; PT 95880 B 19980731

DOCDB simple family (application)

EP 90121582 A 19901112; AT 90121582 T 19901112; DE 69003223 T 19901112; DK 90121582 T 19901112; ES 90121582 T 19901112; FR 8914915 A 19891114; PT 9588090 A 19901113