

Title (en)

Adjustable mounting flange for proximity detector.

Title (de)

Verstellbarer Flansch zur Montage eines Näherungssensors.

Title (fr)

Bride de montage réglable pour détecteur de proximité.

Publication

EP 0428426 B1 19950802 (FR)

Application

EP 90403007 A 19901025

Priority

FR 8914413 A 19891103

Abstract (en)

[origin: EP0428426A1] Flange for supporting and for adjusting the position of a proximity detector. <??>The body (21) of the flange has a cylindrical housing (22) in which the case (11) of the detector is held by clamp means (23). Fastening means (24) are provided on the side of the body (21) to allow it to be adjusted along the axis of the housing. The body (21) comprises a thin rigid cover (25) at one end of the housing to act as an end-stop to a detection side (12) of the case. <IMAGE>

IPC 1-7

G12B 9/08

IPC 8 full level

F16B 9/02 (2006.01); **G12B 9/00** (2006.01); **H01H 9/02** (2006.01)

CPC (source: EP US)

G12B 9/00 (2013.01 - EP US); **H01H 9/0207** (2013.01 - EP US); **Y10T 403/535** (2015.01 - EP US); **Y10T 403/7041** (2015.01 - EP US)

Cited by

EP0645789A1; EP0657905A1; FR2713875A1; DE19641137A1; DE19641137C2

Designated contracting state (EPC)

CH DE GB IT LI SE

DOCDB simple family (publication)

EP 0428426 A1 19910522; **EP 0428426 B1 19950802**; BR 9005576 A 19910917; DE 69021330 D1 19950907; DE 69021330 T2 19960111; FR 2654162 A1 19910510; FR 2654162 B1 19920214; JP H03223511 A 19911002; US 5123769 A 19920623

DOCDB simple family (application)

EP 90403007 A 19901025; BR 9005576 A 19901101; DE 69021330 T 19901025; FR 8914413 A 19891103; JP 29877690 A 19901102; US 60892790 A 19901105