

Title (en)

INSTALLATION FOR ELECTROSTATICALLY APPLYING A CONDUCTIVE COATING PRODUCT

Publication

EP 0428435 B1 19930526 (FR)

Application

EP 90403141 A 19901106

Priority

FR 8914912 A 19891114

Abstract (en)

[origin: EP0428435A1] The installation comprises a high-voltage part and an earthed part which are separated by at least one temporary isolation device. <??>According to the invention, the electrostatic sprayer (11) is supplied by a first tank (20) which is isolated and the latter is filled in a very short time by the coating product previously stored in a second tank (30) at earth potential by utilising means (50, 54, 56) for rapidly draining the said second tank, via a temporary isolation device (28). <IMAGE>

IPC 1-7

B05B 5/16

IPC 8 full level

B05B 5/08 (2006.01); **B05B 5/16** (2006.01); **B05C 11/10** (2006.01)

CPC (source: EP KR US)

B05B 5/16 (2013.01 - KR); **B05B 5/1625** (2013.01 - EP US); **B05B 5/1666** (2013.01 - EP US); **B05B 5/1675** (2013.01 - EP US)

Cited by

EP1772194A3; DE19640015A1; DE19640015C2; US8020784B2; US6422491B1; WO9932231A1; EP1772194A2; EP2810719B1

Designated contracting state (EPC)

BE DE ES GB IT NL SE

DOCDB simple family (publication)

EP 0428435 A1 19910522; **EP 0428435 B1 19930526**; CA 2029606 A1 19910515; CA 2029606 C 19990713; DE 69001744 D1 19930701; DE 69001744 T2 19931111; ES 2040578 T3 19931016; FR 2654365 A1 19910517; FR 2654365 B1 19920221; JP H03178354 A 19910802; KR 0124188 B1 19971125; KR 910009339 A 19910628; US 5094389 A 19920310

DOCDB simple family (application)

EP 90403141 A 19901106; CA 2029606 A 19901108; DE 69001744 T 19901106; ES 90403141 T 19901106; FR 8914912 A 19891114; JP 30635190 A 19901114; KR 900017372 A 19901029; US 60673090 A 19901031