

Title (en)  
BOGIE WITH GUIDED WHEELSETS

Publication  
**EP 0429095 B1 19930602 (DE)**

Application  
**EP 90123416 A 19880906**

Priority  
DE 3730180 A 19870909

Abstract (en)  
[origin: EP0306889A2] The bogie has a frame (8) with an axle at each end. Each axle is supported in bearings (2) mounted on springs (7) so that each bearing has a limited degree of longitudinal movement w.r.t the frame. Each bearing (2) is connected by a pivoted link (5) to one end of a central link (9) which is pivoted to the frame. The linkages are so arranged that the two bearings on the same side of the frame either move simultaneously towards each other or away from each other.

IPC 1-7  
**B61F 5/38**

IPC 8 full level  
**B61F 5/38** (2006.01)

CPC (source: EP)  
**B61F 5/38** (2013.01)

Cited by  
KR100657622B1; WO2007007930A1

Designated contracting state (EPC)  
AT BE CH FR GB LI NL

DOCDB simple family (publication)  
**EP 0429095 A1 19910529; EP 0429095 B1 19930602**; AT E78441 T1 19920815; AT E90047 T1 19930615; DE 3730180 A1 19890330; DE 3730180 C2 19900613; EP 0306889 A2 19890315; EP 0306889 A3 19890906; EP 0306889 B1 19920722

DOCDB simple family (application)  
**EP 90123416 A 19880906**; AT 88114499 T 19880906; AT 90123416 T 19880906; DE 3730180 A 19870909; EP 88114499 A 19880906