

Title (en)

Solid dielectric capacitor and method of manufacture.

Title (de)

Festdielektrikum-Kondensator und Verfahren zur Herstellung.

Title (fr)

Condensateur à diélectrique solide et son procédé de fabrication.

Publication

EP 0430179 A2 19910605 (EN)

Application

EP 90122665 A 19901127

Priority

- JP 31109689 A 19891130
- JP 31109789 A 19891130

Abstract (en)

A monolithic capacitor having a dielectric ceramic body cosintered with at least two base metal electrodes. The ceramic body is composed of a major ingredient expressed by the formula, $(1 - \alpha) \{ (\text{Ba}_{1-x}\text{M}_x)\text{O}(\text{Ti}_{1-y}\text{R}_y)\text{O}_2 - (y/2) \} + \alpha \text{CaZrO}_3$ where M is either or both of magnesium and zinc, R is a rare earth element or elements, and α , k, x and y are numerals in specified ranges. To this major ingredient is added a minor proportion of an additive. The additive is a mixture of boric oxide or lithium oxide, silicon dioxide and at least one metal oxide selected from among barium oxide, strontium oxide, calcium oxide, magnesium oxide and zinc oxide. For the fabrication of capacitors the mixture of the above major ingredient and additives in finely divided form are formed into moldings of desired shape and size, each with at least two electrodes buried therein. The moldings and electrodes are cosintered in a reductive or neutral atmosphere at temperatures of less than 1200 degrees C. and then are heated at a lower temperature in an oxidative atmosphere. <IMAGE>

IPC 1-7

C04B 35/49; H01G 4/12

IPC 8 full level

C04B 35/49 (2006.01); **H01G 4/12** (2006.01)

CPC (source: EP KR US)

C04B 35/49 (2013.01 - EP US); **H01G 4/12** (2013.01 - KR); **H01G 4/1245** (2013.01 - EP US); **Y10T 29/435** (2015.01 - EP US)

Cited by

US5326721A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0430179 A2 19910605; EP 0430179 A3 19911121; EP 0430179 B1 19940608; DE 69009694 D1 19940714; DE 69009694 T2 19950112; KR 910010556 A 19910629; KR 930004743 B1 19930603; US 5075819 A 19911224

DOCDB simple family (application)

EP 90122665 A 19901127; DE 69009694 T 19901127; KR 900019602 A 19901130; US 61865590 A 19901127