

Title (en)  
ROTARY MACHINE WITH ROLLING PISTON

Publication  
**EP 0430789 B1 19930804 (FR)**

Application  
**EP 90403344 A 19901127**

Priority  
FR 8915654 A 19891128

Abstract (en)  
[origin: CA2029796A1] The rotary machine comprises a cylindrical chamber having a rolling piston rotating therein, the piston rolling against the inside surface of the chamber wall. In normal operation, springs keep a vane pressed against the periphery of the rolling piston. A control device for controlling the piston of the vane comprises a control rod lying in the same plane as the vane. The rod includes a retaining abutment formed at the bottom of the control rod and received in a housing formed inside the vane and including a top wall through which the control rod passes, the top wall co-operating with the abutment and the housing having a vertical extent which is not less than the maximum distance between the peripheral surface of the piston and the casing of the rotary machine, thereby enabling the vane to move freely relative to the abutment when the abutment is in its low position. Means for selectively controlling the rod enable the vane to be moved to a disengaged position in which it is no longer in permanent contact with the peripheral surface of the rolling piston, thereby preventing the rotary machine from operating at full load.

IPC 1-7  
**F01C 21/16**

IPC 8 full level  
**F04C 2/356** (2006.01); **F01C 1/356** (2006.01); **F01C 20/06** (2006.01); **F03C 1/40** (2006.01); **F03C 2/30** (2006.01); **F04C 2/30** (2006.01); **F04C 18/356** (2006.01)

CPC (source: EP US)  
**F01C 20/06** (2013.01 - EP US)

Cited by  
CN105164374A; CN111412139A; WO2014095294A3

Designated contracting state (EPC)  
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0430789 A1 19910605; EP 0430789 B1 19930804**; AT E92589 T1 19930815; CA 2029796 A1 19910529; DE 69002591 D1 19930909; FR 2655093 A1 19910531; JP H03179188 A 19910805; US 5131826 A 19920721

DOCDB simple family (application)  
**EP 90403344 A 19901127**; AT 90403344 T 19901127; CA 2029796 A 19901113; DE 69002591 T 19901127; FR 8915654 A 19891128; JP 32877590 A 19901128; US 61891890 A 19901128