

Title (en)
PROTECTIVE DOOR FITTING

Publication
EP 0431717 A3 19910925 (DE)

Application
EP 90250305 A 19901206

Priority
DE 8914633 U 19891208

Abstract (en)
[origin: EP0431717A2] The invention relates to a protective fitting, consisting of an outer plate and an inner plate which each have a recess for the lock cylinder to be inserted between the two plates, and with a bushing for a handle, knob or the like. To simplify the stockkeeping of protective fittings of this type, it is proposed that the recess be designed as an elongate cutout (1), the length of which is selected so that the lock cylinder can be inserted with its cylinder centre at a distance of 72 or 92 mm from the handle centre, and that an insert matched to the cutout (1) of the outer plate (2) be insertable into this in two positions according to the abovementioned different distances. <IMAGE>

IPC 1-7
E05B 15/02

IPC 8 full level
E05B 15/02 (2006.01)

CPC (source: EP)
E05B 15/02 (2013.01)

Citation (search report)
• [X] DE 3234512 A1 19840322 - JANS FRANZ WERNER [DE]
• [A] DE 121758 C
• [A] DE 304960 C

Cited by
US6035678A; DE29719726U1; DE19805497C1; GB2616059A; US6584818B2; US6612141B2

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL

DOCDB simple family (publication)
DE 8914633 U1 19900208; EP 0431717 A2 19910612; EP 0431717 A3 19910925

DOCDB simple family (application)
DE 8914633 U 19891208; EP 90250305 A 19901206