

Title (en)  
PRINTER HEAD

Publication  
**EP 0431876 A3 19911204 (EN)**

Application  
**EP 90313117 A 19901203**

Priority  
JP 31470989 A 19891204

Abstract (en)  
[origin: EP0431876A2] A printer head consists of a yoke (11), magnet members (12) mounted to the yoke, a base plate (14) attached to the front of the yoke (11), and a plurality of head pins (17) provided between the yoke (11) and the base plate (14). In this printer head, the head pins (17) are arranged in straight rows, which are inclined at a specified angle to the direction of stroke of the printer head. The base plate (14) is formed with a plurality of through-holes (18) at positions corresponding to the head pins so that the head pins can be advanced and retracted through the through-holes (18) by the action of the magnet circuit. <IMAGE>

IPC 1-7  
**B41J 2/26**

IPC 8 full level  
**B41J 2/24** (2006.01); **B41J 2/255** (2006.01); **B41J 2/28** (2006.01)

CPC (source: EP)  
**B41J 2/24** (2013.01)

Citation (search report)

- [Y] US 4484519 A 19841127 - KURIHARA TOSHIO [JP], et al
- [A] US 4544288 A 19851001 - SUZUKI HIROFUMI [JP], et al
- [A] WO 7900627 A1 19790906 - SINOTO N
- [A] US 4527469 A 19850709 - WOLF PETER H [US], et al
- [Y] PATENT ABSTRACTS OF JAPAN vol. 11, no. 372 (M-648)(2819) 4 December 1987 & JP-A-62 146 645 ( M. UKAI ) 30 June 1987
- [YP] & US 4 936 210(M. UKAI)
- [A] IBM TECHNICAL DISCLOSURE BULLETIN. vol. 24, no. 10, March 1982, NEW YORK US pages 4981 - 4982; W.J. THORNHILL: 'Rotatable wire matrix printhead'
- [A] IBM TECHNICAL DISCLOSURE BULLETIN. vol. 23, no. 1, June 1980, NEWYORK US page s 44 - 45; J.E. LISINSKI E.A.: 'Double density line printer magnet assembly'

Cited by  
US6682233B2

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**EP 0431876 A2 19910612; EP 0431876 A3 19911204; JP H03175054 A 19910730**

DOCDB simple family (application)  
**EP 90313117 A 19901203; JP 31470989 A 19891204**