

Title (en)
DOORFRAME OUT OF METAL PROFILE AND COVER

Publication
EP 0433760 B1 19930217 (DE)

Application
EP 90123266 A 19901205

Priority
DE 8914908 U 19891219

Abstract (en)
[origin: EP0433760A1] To avoid the exceptionally complicated cross-sections of the metal profiles used thus far of a doorframe, the L-shaped basic configuration of the metal profile (4) is extended rectilinearly into a T-profile cross-section. One half (wall half 5a) of the T-beam (5) is connected to the wall lining (17) and delimits it on the doorleaf side. The other half (soffit half 5b) of the T-beam (5) is connected to the soffit lining (16) and bears on its underside a wall strut (7). Perforations (10) for fastening the metal profile (4) to the masonry (8) are made in the @-shaped wall strut (7).
<IMAGE>

IPC 1-7
E06B 1/32

IPC 8 full level
E06B 1/32 (2006.01); **E06B 1/52** (2006.01)

CPC (source: EP)
E06B 1/32 (2013.01); **E06B 1/52** (2013.01)

Cited by
CN111891158A

Designated contracting state (EPC)
AT BE CH DE FR IT LI LU NL

DOCDB simple family (publication)
EP 0433760 A1 19910626; EP 0433760 B1 19930217; AT E85836 T1 19930315; DE 59000898 D1 19930325; DE 8914908 U1 19900201

DOCDB simple family (application)
EP 90123266 A 19901205; AT 90123266 T 19901205; DE 59000898 T 19901205; DE 8914908 U 19891219