Title (en)

PROTECTION FOR AWNING PROJECTION

Publication

EP 0434545 B1 19930915 (FR)

Application

EP 90403645 A 19901218

Priority

FR 8916770 A 19891219

Abstract (en)

[origin: EP0434545A1] The awning comprises a canopy for protecting the wound fabric and is of the type comprising, on the one hand, a stationary carrier structure (1) for a fabric-carrying roller (16) and articulated arms (6) and, on the other hand, a fabric (8) which is fixed by one of its ends to the fabric-carrying roller (16) and by the other of its ends to a load bar (7) which is fixed to the end of articulated arms (6) so that the fabric (8) can be wound over the fabric-carrying roller (16) or unwound from the latter, in order to be extended in a plane which is inclined to a greater or lesser extent. It is characterised in that it comprises an awning, separate and independent from the carrier structure (1), which is extended from the rear portion of the roller (16), and on top of this roller (16), in a front plane (21) limited by one edge overhanging at least as far in front of the roller (16) as is the load bar (7) when the fabric (8) is in the wound position, means being provided for locking the canopy in a position which is advantageously adjustable in relation to the stationary carrier structure (1), in which position its front plane is parallel to the fabric (8). <IMAGE>

IPC 1-7

E04F 10/06

IPC 8 full level

E04F 10/06 (2006.01)

CPC (source: EP)

E04F 10/0618 (2013.01); E04F 10/0637 (2013.01); E04F 10/0662 (2013.01); E04F 10/0674 (2013.01); E04F 10/0685 (2013.01)

Cited by

FR2755714A1; FR2688534A1; FR2708954A1; EP1548203A3; WO2004029381A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0434545 A1 19910626; EP 0434545 B1 19930915; AT E94605 T1 19931015; DE 69003367 D1 19931021; FR 2656022 A1 19910621

DOCDB simple family (application)

EP 90403645 A 19901218; AT 90403645 T 19901218; DE 69003367 T 19901218; FR 8916770 A 19891219