

Title (en)
Light.

Title (de)
Licht.

Title (fr)
Eclairage.

Publication
EP 0434649 A2 19910626 (EN)

Application
EP 90850373 A 19901115

Priority
US 45215789 A 19891218

Abstract (en)
Light, which includes a reflector (103), batteries (105, 107) and a light emitting diode (102). The light emitting diode and the batteries are hermetically encased between a glass (103), that also serves as a reflector, and a rear wall (113) of the light. The batteries and the light emitting diode are connected in series with two metallic plates (108, 109) that extend through the rear wall (113) of the light. When the light is mounted on its bracket (115) that in turn is fastened to for instance a bicycle this fastening bracket is metallic and contacts the plates closing the circuit and lighting the light emitting diode. Due to the high efficiency of the light emitting diode it will be capable to burn a very long time before the batteries have to be changed and since the light in order to be lighted or unlighted is mounted or demounted possible oxide layers will always be worn away by this motion. <IMAGE>

IPC 1-7
B62J 6/00

IPC 8 full level
B60R 16/04 (2006.01); **B62J 6/00** (2006.01); **H01L 33/30** (2010.01); **H01L 33/48** (2010.01); **H01L 33/60** (2010.01)

CPC (source: EP US)
B62J 6/01 (2020.02 - EP US); **Y10S 362/80** (2013.01 - EP US)

Cited by
ES2056713A2

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0434649 A2 19910626; **EP 0434649 A3 19920311**; JP H04252785 A 19920908; US 5029055 A 19910702

DOCDB simple family (application)
EP 90850373 A 19901115; JP 40269390 A 19901217; US 45215789 A 19891218