

Title (en)

Method and apparatus for setting a given withwise tension to a moving sheet-like material.

Title (de)

Verfahren und Anordnung zur Einstellung einer definierten Spannung in breitgeföhrten laufenden Warenbahnen.

Title (fr)

Procédé et installation pour imposer une tension transversale définie à une matière en bande en déplacement.

Publication

**EP 0436150 B1 19941019 (DE)**

Application

**EP 90123717 A 19901210**

Priority

DE 3940850 A 19891211

Abstract (en)

[origin: EP0436150A1] The invention relates to a method for setting a uniform and specific tension in running material webs, such as textile webs or the like, guided with width stretching through a treatment space, especially a dryer, in which the material webs are first introduced without width stretching into tensioning elements which are arranged on tensioning chains guided in chain tracks, and are subsequently width-stretched by a width adjustment of the chain tracks, and is aimed at guaranteeing an always specific tension in all the parts of the material web. For this, it is proposed, according to the invention, to guide the material webs (10) through the treatment station so as to be held elastically flexibly in the width-stretching direction, for example in that the tensioning elements (14), such as needle bars or tenter clips, arranged on carriers (13) on the tensioning chains and held in an end position in the width-stretching direction of the material web, are mounted on the carriers in an elastically displaceable manner.

IPC 1-7

**D06C 3/02**

IPC 8 full level

**D06C 3/02** (2006.01)

CPC (source: EP)

**D06C 3/02** (2013.01)

Citation (examination)

DE 1629384 C2 19720309 - DETAG

Cited by

EP0819642A3; DE4316072C2; DE4316072C5

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0436150 A1 19910710; EP 0436150 B1 19941019; AT E113090 T1 19941115; DE 3940850 A1 19910613; DE 3940850 C2 19941027;**  
DE 59007505 D1 19941124

DOCDB simple family (application)

**EP 90123717 A 19901210; AT 90123717 T 19901210; DE 3940850 A 19891211; DE 59007505 T 19901210**