

Title (en)

DEVICE AND ITS APPLICATION IN THE ERECTION OF DRY PARTITION

Publication

EP 0439060 A3 19930407 (DE)

Application

EP 91100524 A 19910117

Priority

DE 4002192 A 19900125

Abstract (en)

[origin: EP0439060A2] The invention relates to a device and its application in the erection of a multilayered solid dry partition in the interior of a building in horizontal succession, consisting of at least one gypsum plasterboard layer or the like, a gas or foamed concrete slab layer and a further gypsum plasterboard layer or the like, it being possible to arrange in each case between the gypsum plasterboard layer and the gas or foamed concrete layer, brick/pumice layer or the like, a sound- and/or heat-insulating layer made, for example, from mineral wool sheets, corrugated paper or the like, and it being possible to fill the lateral and upper connection joints with polyurethane foam and/or mineral wool and/or mortar, having a demountable constructing framework which can be clamped between the ceiling bay and the floor slab of an interior room and to which the slab parts of the first dry-partition layer can be fastened.

IPC 1-7

E04B 2/82; E04B 2/72

IPC 8 full level

E04B 2/74 (2006.01); **E04B 2/82** (2006.01); **E04G 21/18** (2006.01); **E04B 2/72** (2006.01)

CPC (source: EP)

E04B 2/7403 (2013.01); **E04B 2/825** (2013.01); **E04G 21/1891** (2013.01); **E04B 2/723** (2013.01)

Citation (search report)

- [A] DE 1993684 U 19680912 - OSTERLOH FA FRITZ [DE]
- [A] DD 267529 A1 19890503 - BMK INGENIEUR HOCHBAU BERLIN V [DD]
- [A] CH 378516 A 19640615 - JODER HERMANN [CH], et al

Cited by

EP1070798A3; CH706217A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0439060 A2 19910731; EP 0439060 A3 19930407; DE 4002192 C1 19910814

DOCDB simple family (application)

EP 91100524 A 19910117; DE 4002192 A 19900125