

Title (en)
PROTECTION COVER FOR A FLORENTINE BLIND

Publication
EP 0439702 B1 19930929 (DE)

Application
EP 90121542 A 19901110

Priority
DE 9000939 U 19900129

Abstract (en)
[origin: US5121782A] The protective covering for a marquee consists of a casing (22) carrying a winding shaft and having a discharge opening extending along the entire length of the casing, which can be closed tightly by a top flap (42) and a bottom flap (46). Top flap (42) is pivoted upward during the discharge of the marquee by its outer tube (14) counter to the force of gravity and following the re-entry of the marquee drops back into its closed position. Bottom flap (46) drops during the discharge of the marquee by its own specific gravity into open position and is drawn back into closed position at the end of the re-entry movement by means of closing levers (76) remaining in the movement path of the outer tube. The quite small top flap (42) cleans off the marquee, but loads it with only a slight weight. The pressure of the outer tube (14) against the closing levers (76) holds flaps (42, 46) dependably closed tightly in the re-entry position/closed position.

IPC 1-7
E04F 10/06

IPC 8 full level
E04F 10/06 (2006.01)

CPC (source: EP US)
E04F 10/0618 (2013.01 - EP US); **E04F 10/0622** (2013.01 - EP US); **E04F 10/0662** (2013.01 - EP US); **E04F 10/0688** (2013.01 - EP US)

Cited by
DE202016104657U1; EP0590249A3; US5351736A; EP0595741A1; EP0576829A1; US5333663A

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
US 5121782 A 19920616; AT E95263 T1 19931015; DE 59002943 D1 19931104; DE 9000939 U1 19900412; DK 0439702 T3 19940221; EP 0439702 A1 19910807; EP 0439702 B1 19930929; ES 2045720 T3 19940116

DOCDB simple family (application)
US 64548891 A 19910124; AT 90121542 T 19901110; DE 59002943 T 19901110; DE 9000939 U 19900129; DK 90121542 T 19901110; EP 90121542 A 19901110; ES 90121542 T 19901110