

Title (en)  
FUEL INJECTION PUMP

Publication  
**EP 0439769 B1 19930908 (DE)**

Application  
**EP 90124332 A 19901215**

Priority  
DE 4002612 A 19900130

Abstract (en)  
[origin: EP0439769A1] A fuel injection pump for internal combustion engines has a pump piston (12) defining a pump working chamber (15), which piston can be driven by way of a cam mechanism (14) in a reciprocating and at the same time rotational movement, during its intake stroke filling the pump working chamber (15) with fuel by way of an inlet (42), which it controls as a function of the angle of rotation. An injection timing device (30), as a function of the speed, rotates the position of the lifting curve of the pump piston (12) relative to its rotational position to "advance" in the case of high speed and "retard" in that of falling speed. In order to enlarge the injection timing range without varying the cam geometry and/or to increase the cam length without varying the injection timing range, a non-return valve (43) with closing direction towards the inlet (42) is arranged between the inlet (42) and the pump working chamber (15) and the control of the inlet (42) by the pump piston (12) is so designed that, when its lifting curve is in the advance position, the pump piston (12) does not close the inlet (42) until it is inside the rising edge. <IMAGE>

IPC 1-7  
**F02M 41/12**

IPC 8 full level  
**F02M 41/12** (2006.01)

CPC (source: EP)  
**F02M 41/12** (2013.01); **F02M 41/121** (2013.01); **F02M 41/123** (2013.01); **F02M 41/128** (2013.01)

Designated contracting state (EPC)  
DE FR GB IT

DOCDB simple family (publication)  
**EP 0439769 A1 19910807**; **EP 0439769 B1 19930908**; DE 4002612 A1 19910801; DE 59002651 D1 19931014; JP 3056263 B2 20000626; JP H051636 A 19930108

DOCDB simple family (application)  
**EP 90124332 A 19901215**; DE 4002612 A 19900130; DE 59002651 T 19901215; JP 764391 A 19910125