

Title (en)

Device for driving the reed in a loom, method for driving the reed and loom with such a device.

Title (de)

Vorrichtung und Verfahren zur Steuerung der Weblade einer Webmaschine und mit dieser Vorrichtung ausgerüstete Webmaschine.

Title (fr)

Dispositif et procédé pour la commande du battant d'un métier à tisser, et métier utilisant un tel dispositif.

Publication

EP 0440579 A1 19910807 (EN)

Application

EP 91810036 A 19910116

Priority

JP 2300790 A 19900201

Abstract (en)

The device for driving the reed (13) in a loom is completely independent from the main motor (40). A separate motor (30) for driving the rocking shaft (10) on which the reed (13) is fixed, is controlled according to the desired individual operating conditions by a control system (50, 57). The method of driving the reed (13) consists in driving the rocking shaft (10) with the reed (13) independently from the main motor (40) for driving other systems of the loom. The loom is including an individual drive (30) for the rocking shaft (10) with the reed (13). <IMAGE>

IPC 1-7

D03D 49/60

IPC 8 full level

D03D 49/60 (2006.01)

CPC (source: EP)

D03D 49/60 (2013.01); **D03D 49/64** (2013.01); **D03D 51/005** (2013.01)

Citation (search report)

- [X] DE 3723433 A1 19881020 - TEXTILMA AG [CH]
- [Y] US 4625768 A 19861202 - PAUWELS BERNARD J [BE], et al
- [A] FR 2359917 A1 19780224 - GAGEY ETIENNE [FR]
- [A] US 3822726 A 19740709 - KUSTER H, et al
- [A] FR 1451236 A 19660107
- [A] EP 0298454 A1 19890111 - NISSAN MOTOR [JP]

Cited by

CZ302120B6; EP0521244A1; CN105755652A; CN105755653A; DE19924627C1; CN102560834A; DE4111405A1; CN101831752A; DE10252053A1; DE10021520A1; EP1152077A3; CN112816402A; US7481249B2; US6418972B2; US6913044B2; WO2005038113A1; WO2004035891A3

Designated contracting state (EPC)

BE DE FR IT

DOCDB simple family (publication)

EP 0440579 A1 19910807; **EP 0440579 B1 19960710**; DE 69120692 D1 19960814; DE 69120692 T2 19970220; JP 2975387 B2 19991110; JP H03227429 A 19911008

DOCDB simple family (application)

EP 91810036 A 19910116; DE 69120692 T 19910116; JP 2300790 A 19900201