

Title (en)

FLAT TILE FOR ROOF

Publication

**EP 0440830 B1 19930908 (DE)**

Application

**EP 90102194 A 19900205**

Priority

EP 90102194 A 19900205

Abstract (en)

[origin: EP0440830A1] A flat-roof pantile has side-groove ribs (9, 10, 24), running in a straight line over the full height to the tile foot, on a plane side-groove section (11) for a double side interlocking joint (2), a tile middle section (1), at least one covering bead (7), an outer head-groove rib (12) running continuously over the width of the tile including a narrow head-corner cutout (4), an outer foot-groove rib (19) running continuously at least up to a narrow foot-corner cutout (5), and an inner foot-groove rib (20). In order to maintain, in such a flat-roof pantile, maximum longitudinal displaceability with complete sealing in the roofing, even for flat roofs of extremely low pitch, the side-groove section (2), which is open towards the tile foot and in the tile-head region towards the tile middle section (1), is arranged so as to be raised relative to the tile middle section (1), an inner head-groove rib (14) capable of being overlapped by the inner foot-groove rib (20) and having at least one perforation (15) is provided, and the outer foot-groove rib is passed round the foot-corner cutout (5) to the tile side edge. <IMAGE>

IPC 1-7

**E04D 1/04**

IPC 8 full level

**E04D 1/04** (2006.01)

CPC (source: EP US)

**E04D 1/2916** (2019.07 - EP US); **E04D 1/2918** (2019.07 - EP US); **E04D 1/2949** (2019.07 - EP US); **E04D 1/2956** (2019.07 - EP US)

Cited by

EP0907209A1; EP0997588A1; EP0718449A1

Designated contracting state (EPC)

AT BE CH DE DK FR GB IT LI LU NL

DOCDB simple family (publication)

**EP 0440830 A1 19910814; EP 0440830 B1 19930908**; AT E94248 T1 19930915; DE 59002653 D1 19931014; DK 0440830 T3 19931108

DOCDB simple family (application)

**EP 90102194 A 19900205**; AT 90102194 T 19900205; DE 59002653 T 19900205; DK 90102194 T 19900205