

Title (en)

FAST ELECTROMAGNETIC TRIP UNIT FOR ELECTRICAL SWITCHING DEVICES

Publication

EP 0442311 A3 19920819 (DE)

Application

EP 91101015 A 19910126

Priority

DE 4004359 A 19900213

Abstract (en)

[origin: EP0442311A2] Fast electromagnetic trip units having impact armature plungers and an electrical trip coil, through whose winding a load current flows, have a relatively large-volume permanent magnet which holds the impact armature plunger, which consists of a ferromagnetic material, in the stressed position against the influence of a storage compression spring. As a result of the high retention force of the permanent magnet, the behaviour of the spring characteristic of the storage compression spring is influenced unfavourably on stressing of the trip unit. The fast trip unit is thus constructed such that, on stressing of the trip unit, on the one hand a favourable behaviour of the spring characteristic is produced and, on the other hand, a high retention force is produced with a minimal magnet volume. This is achieved by a magnet core (4) in the form of a tubular sleeve consisting of a ferromagnetic material projecting from the lower pole plate (5) of the magnet housing (3) and passing coaxially through the trip coil (2) over its entire length, the impact armature plunger (6) consisting of a non-magnetic material and the permanent magnet (8) being arranged on the impact armature plunger (6) above the trip coil (2), with an air gap (20) opposite the wall of the housing (3), such that, when the fast trip unit is in the stressed state, the magnetic circuit (22) from the permanent magnet (8) is closed via the magnetic core (4), the lower pole plate (5) and a lower part (3a) of the housing (3) surrounding the trip coil (2), while, in the unstressed or tripped state, the magnetic circuit (22a) is short-circuited between the permanent magnet (8) and an upper, narrower housing projection (15). As a result of such a design, the assembly of the quick trip unit can also be considerably simplified and hence made more cost-effectively. <IMAGE>

IPC 1-7

H01H 71/32

IPC 8 full level

H01H 71/32 (2006.01)

CPC (source: EP)

H01H 71/322 (2013.01)

Citation (search report)

- [A] FR 2344948 A1 19771014 - MERLIN GERIN [FR]
- [A] DE 8806830 U1 19880728

Cited by

WO2011043808A1; CN112017919A; JP2016051708A; CN102612728A; EP0841669A1; EP1137032A3; GB2260445A; GB2260445B; US6424244B1; US8581682B2

Designated contracting state (EPC)

BE DE ES FR GB IT NL SE

DOCDB simple family (publication)

EP 0442311 A2 19910821; EP 0442311 A3 19920819; EP 0442311 B1 19950510; DE 4004359 A1 19910814; DE 59105408 D1 19950614; ES 2073597 T3 19950816

DOCDB simple family (application)

EP 91101015 A 19910126; DE 4004359 A 19900213; DE 59105408 T 19910126; ES 91101015 T 19910126