

Title (en)
SAFETY CATCH FOR A CARRIAGE GUIDED ALONG STAIR RAIL

Publication
EP 0442429 A3 19920219 (DE)

Application
EP 91101901 A 19910211

Priority
DE 4004190 A 19900212

Abstract (en)
[origin: EP0442429A2] The carriage guided on a stair rail is equipped with a solid catch lever (28) which is pivotably arranged transversely to the travel direction (32) so close to the stair rail that it can swing with its descent-side lever arm (39) against the action of a tension spring (34) into the area between two adjacent rungs (7) and (7a) which are arranged on the stair rail perpendicularly to the travel direction (32). The tension spring (34) attempts to move the catch lever (28) into a position pointing in the travel direction (32). On its longitudinal side pointing towards the stair rail, the catch lever (28) has on its ascent-side arm a lobe-like projection (45) which pivots the catch lever (28) during descending travel on each rung (7) in such a way that the descent-side arm of the catch lever (39) enters the intermediate space relative to the next rung (7). If the descending travel exceeds a predetermined speed, the catch lever (28), on account of its inertia, cannot escape quickly enough from the area of the rungs (7) and stops the carriage. <IMAGE>

IPC 1-7
B66B 9/08; **B66B 5/04**

IPC 8 full level
B66B 5/04 (2006.01); **B66B 9/08** (2006.01)

CPC (source: EP)
B66B 9/0815 (2013.01)

Citation (search report)
• [A] US 4046226 A 19770906 - FLINCHBAUGH HENRY K
• [A] EP 0137577 A1 19850417 - STOPHER ANTONY
• [A] US 4179012 A 19791218 - HEBERLE HEINZ [DE]
• [A] GB 2184707 A 19870701 - EASE LIMITED

Cited by
CN102936959A; US6659230B1

Designated contracting state (EPC)
DE GB NL SE

DOCDB simple family (publication)
EP 0442429 A2 19910821; **EP 0442429 A3 19920219**; **EP 0442429 B1 19941130**; DE 59103604 D1 19950112

DOCDB simple family (application)
EP 91101901 A 19910211; DE 59103604 T 19910211