

Title (en)
RETARDER OF THE LUBRICANT FLOW

Publication
EP 0443092 B1 19930414 (DE)

Application
EP 90120044 A 19901019

Priority
DE 4001467 A 19900119

Abstract (en)
[origin: EP0443092A1] A lubricant flow retarder arranged in the case of an internal combustion engine is arranged adjacent to or in a surface adjoining an oil sump. It prevents foamed oil from being sucked up immediately because it has oil openings along its edge but otherwise separates the spaces lying above and below the retarder from one another. The oil reaches the strainer in a delayed fashion and is thus degasified. <IMAGE>

IPC 1-7
F01M 11/00

IPC 8 full level
F01M 1/06 (2006.01); **F01M 11/00** (2006.01)

CPC (source: EP US)
F01M 11/0004 (2013.01 - EP US); **F01M 2011/0062** (2013.01 - EP US)

Designated contracting state (EPC)
DE ES FR GB IT NL SE

DOCDB simple family (publication)
EP 0443092 A1 19910828; EP 0443092 B1 19930414; DE 4001467 A1 19910725; DE 4001467 C2 19911114; DE 59001205 D1 19930519; ES 2040018 T3 19931001; JP H04330311 A 19921118; US 5161643 A 19921110

DOCDB simple family (application)
EP 90120044 A 19901019; DE 4001467 A 19900119; DE 59001205 T 19901019; ES 90120044 T 19901019; JP 330391 A 19910116; US 64254091 A 19910117