

Title (en)
DETECTOR DEVICE FOR COUPLED CONNECTOR

Publication
EP 0449122 A3 19930407 (EN)

Application
EP 91104468 A 19910321

Priority
• JP 7206390 A 19900323
• JP 11511590 A 19900502
• JP 11511690 A 19900502

Abstract (en)
[origin: EP0449122A2] A detector circuit for coupled connectors is provided with one connector housing, the other connector housing and a lock confirming slider. A sensor circuit terminal and a short-circuiting terminal are oppositely arranged in respect to the one connector housing and the lock confirming slider. Springs are arranged between the terminals. The lock confirming slider is moved forward by the springs when both connector housings are completely fitted to each other. Thus, the sensor circuit terminal and the short-circuiting terminal are contacted to each other. <IMAGE>

IPC 1-7
H01R 13/629

IPC 8 full level
H01R 13/641 (2006.01)

CPC (source: EP US)
H01R 13/641 (2013.01 - EP US)

Citation (search report)
• [Y] US 4878853 A 19891107 - YAMADE KENICHI [JP], et al
• [Y] US 4634204 A 19870106 - DETTER GARY C [US], et al
• [A] EP 0300767 A2 19890125 - SUMITOMO WIRING SYSTEMS [JP]

Cited by
EP0655807A3; EP1662620A3; EP4435979A1; JP2019079638A; EP3703196A4; US11245228B2; US11843200B2; WO2006081901A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0449122 A2 19911002; EP 0449122 A3 19930407; EP 0449122 B1 19961204; DE 69123380 D1 19970116; DE 69123380 T2 19970327;
US 5066244 A 19911119; US 5102349 A 19920407

DOCDB simple family (application)
EP 91104468 A 19910321; DE 69123380 T 19910321; US 67393291 A 19910321; US 74814291 A 19910821