

Title (en)  
OPERATING DEVICE FOR CIRCUIT BREAKERS

Publication  
**EP 0449148 A3 19920902 (EN)**

Application  
**EP 91104584 A 19910323**

Priority  
SE 9001116 A 19900328

Abstract (en)  
[origin: EP0449148A2] Operating device for circuit breakers comprising a closing spring and an opening spring (2). After each completed closing operation, a motor (16) tensions the closing spring again which, while closing the circuit breaker, tensions the opening spring. The closing spring is kept tensioned by a closing latch (6). The circuit breaker (20) is kept closed and the opening spring (2) is kept tensioned by a trip latch (7). The operating device is composed around only one shaft (3), which provides a simple design with relatively few components. On the shaft (3) a driver lever (4) is fixed. Upon closing of the circuit breaker, the driver lever (4) is connected, by a latching engagement (43,53), to an operating lever (5), connected to the movable contact of the circuit breaker, and pulls said lever along. The operating lever (5) is eccentrically mounted in relation to the shaft (3) in such a way that the levers (4,5) after a certain rotating movement, for example 90 DEG , are disengaged from each other. <IMAGE>

IPC 1-7  
**H01H 3/30**

IPC 8 full level  
**H01H 3/30** (2006.01)

CPC (source: EP)  
**H01H 3/3026** (2013.01); **H01H 3/3042** (2013.01)

Citation (search report)

- [X] EP 0320614 A1 19890621 - SPRECHER ENERGIE AG [CH]
- [A] BE 415906 A 19360731 - ACEC [BE]
- [A] EP 0293909 A2 19881207 - MITSUBISHI ELECTRIC CORP [JP]
- [A] US 4343030 A 19820803 - DATE K HENRY, et al

Cited by  
DE102011089369A1; CN107170592A; CN110729141A; DE10061164C1

Designated contracting state (EPC)  
CH DE FR GB IT LI

DOCDB simple family (publication)  
**EP 0449148 A2 19911002; EP 0449148 A3 19920902; EP 0449148 B1 19950927**; DE 69113302 D1 19951102; DE 69113302 T2 19960515; SE 465902 B 19911111; SE 9001116 D0 19900328; SE 9001116 L 19910929

DOCDB simple family (application)  
**EP 91104584 A 19910323**; DE 69113302 T 19910323; SE 9001116 A 19900328