

Title (en)
Ring laser

Title (de)
Ringlaser

Title (fr)
Laser en anneau

Publication
EP 0452069 B1 19960131 (EN)

Application
EP 91303076 A 19910408

Priority
US 50962790 A 19900413

Abstract (en)

[origin: EP0452069A2] A ring laser (30) is provided with only two reflecting surfaces (34, 36) to define the cavity. A gain medium (32) is located between the reflecting surfaces (34, 36). At least one optical interface (38, 40) is located within the cavity and is oriented such that the beam will be deflected by refraction to create a ring path. The angle of incidence of the beam with the interface (38, 40) should be less than Brewster's angle and the surface should have an antireflective coating. The interface can be located on the lasant material, on a non-linear optical material or on a passive optical element. To achieve unidirectional and single frequency operation, permanent magnets (70) and a quartz rotator plate (74) are provided. When the ring is used for intracavity second harmonic generation, the resultant output is amplitude stable because of the avoidance of mode beating. The second harmonic radiation is generated unidirectionally increasing useable output, by passing the laser beam through a non-linear material (42) within the cavity. <IMAGE>

IPC 1-7
H01S 3/083; H01S 3/109; H01S 3/06

IPC 8 full level
H01S 3/06 (2006.01); **H01S 3/083** (2006.01); **H01S 3/108** (2006.01); **H01S 3/109** (2006.01); **H01S 3/136** (2006.01); **H01S 3/0941** (2006.01)

CPC (source: EP US)
H01S 3/0606 (2013.01 - EP US); **H01S 3/083** (2013.01 - EP US); **H01S 3/109** (2013.01 - EP US); **H01S 3/0615** (2013.01 - EP US);
H01S 3/09415 (2013.01 - EP US)

Cited by
US5557475A; US5636069A; US5798877A; GB2270589A; US5357537A; GB2270589B; US6611343B1; US7065105B2; US6317449B1;
WO9602013A1; WO9949362A1

Designated contracting state (EPC)
CH DE FR GB IT LI

DOCDB simple family (publication)
EP 0452069 A2 19911016; EP 0452069 A3 19921119; EP 0452069 B1 19960131; DE 69116716 D1 19960314; DE 69116716 T2 19960808;
JP 3178729 B2 20010625; JP H04226092 A 19920814; US 5052815 A 19911001

DOCDB simple family (application)
EP 91303076 A 19910408; DE 69116716 T 19910408; JP 10689291 A 19910411; US 50962790 A 19900413