

Title (en)

Eyelet drawn clamp provided with anchoring clip for avoiding losses of pieces.

Title (de)

Gezogene Öseklammer mit Befestigungsklemme um den Verlust von Teilen zu Vermeiden.

Title (fr)

Moyen de serrage d'oeillet étiré avec clip d'ancrage pour éviter les pertes de pièces.

Publication

EP 0453962 A2 19911030 (EN)

Application

EP 91106228 A 19910418

Priority

IT 2105190 U 19900423

Abstract (en)

Eyelet clamp, comprised of a drawn sleeve component (12) insertable on a bar (38) of a terminal (40) of an electric machine or equipment, kept anchored to the bar (38) by a clip (60) consisting of a planar metallic resilient strip (62) from which descend two legs (68, 70) substantially perpendicular to the planar strip (62) and each other parallel, to grasp two sides (72, 74) of a part of the drawn sleeve (12) in order to prevent axial sliding of the sleeve with respect to the bar (38), and provided with an anchoring tang (66) diagonally lifted for engaging a bore (76) of the bar (38) of the terminal (40), needing the tang (66) the specific intervention of a tool to be disengaged from the bore (76) of terminal bar (38). <IMAGE>

IPC 1-7

H01R 4/28; **H01R 4/38**

IPC 8 full level

H01R 4/28 (2006.01); **H01R 4/38** (2006.01)

CPC (source: EP)

H01R 4/28 (2013.01); **H01R 4/366** (2013.01); **H01R 4/38** (2013.01)

Cited by

CN112421280A; FR3035272A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0453962 A2 19911030; **EP 0453962 A3 19920722**; IT 219488 Z2 19930317; IT 9021051 U1 19911024; IT 9021051 V0 19900423

DOCDB simple family (application)

EP 91106228 A 19910418; IT 2105190 U 19900423