

Title (en)
METHOD AND APPARATUS FOR DYEING CARPET SAMPLES

Publication
EP 0456078 A3 19920325 (DE)

Application
EP 91106947 A 19910429

Priority
DE 4014445 A 19900505

Abstract (en)
[origin: EP0456078A2] The laboratory dyeing of samples made of cloth runs must correspond to the continuous dyeing conditions encountered in practice, in order to achieve comparable dyeing results. For this, provision is made to join the sample piece to form a tube and to push it onto a roller which continues to rotate not only during application of the dye but also during the steaming operation. For executing this dyeing-steaming cycle in the laboratory, it is advisable to arrange the dyeing roller on a swivel lever which is pivotable from a dyeing position below the dye application apparatus into a steaming position below a steamer hood. For steaming, the steamer hood merely requires to be moved downwards, in order to immerse the dyeing roller completely in the steam atmosphere. <IMAGE>

IPC 1-7
D06B 23/10

IPC 8 full level
D06B 23/10 (2006.01)

CPC (source: EP US)
D06B 23/10 (2013.01 - EP US)

Citation (search report)
• [A] GB 804259 A 19581112 - BERTIL FREDRICK HELGESON MELLB
• [A] GB 1193233 A 19700528 - TRANSPARENT PAPER LTD

Designated contracting state (EPC)
BE DE GB

DOCDB simple family (publication)
EP 0456078 A2 19911113; EP 0456078 A3 19920325; EP 0456078 B1 19941102; DE 4014445 A1 19911107; DE 59103391 D1 19941208;
US 5214943 A 19930601; US 5274866 A 19940104

DOCDB simple family (application)
EP 91106947 A 19910429; DE 4014445 A 19900505; DE 59103391 T 19910429; US 69602591 A 19910506; US 99141892 A 19921216