

Title (en)

INDICATION METHOD AND CIRCUIT OF DIFFERENT INPUT SIGNALS

Publication

EP 0456080 A3 19930616 (DE)

Application

EP 91106956 A 19910429

Priority

AT 104690 A 19900511

Abstract (en)

[origin: EP0456080A2] A method and a circuit are described for indicating different input signal states, in which a signalling device is activated or deactivated continuously or intermittently. This happens in such a way that levels (U2, U3) are provided for intermittent operation which differ from the levels for continuous activation (U4) or de-activation (U1). <IMAGE>

IPC 1-7

G08B 29/02

IPC 8 full level

G08B 29/02 (2006.01)

CPC (source: EP)

G08B 29/02 (2013.01)

Citation (search report)

- [Y] US 3922569 A 19751125 - NABETANI HIROSHI, et al
- [YD] DE 3147742 A1 19830609 - SIEMENS AG [DE]
- [Y] DE 2729108 B2 19790712
- [Y] US 3944921 A 19760316 - TSUDA SHIN, et al
- [A] DE 2451872 B1 19760311 - SIEMENS AG
- [A] DE 2350362 B2 19750731
- [A] DE 2455656 B1 19750911 - SIEMENS AG
- [A] US 4307389 A 19811222 - SLOTKOWSKI KENNETH G
- [A] GB 1447291 A 19760825 - HONEYWELL LTD

Cited by

EP0562960A1; FR2689279A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0456080 A2 19911113; EP 0456080 A3 19930616; EP 0456080 B1 19960911; AT 398859 B 19950227; AT A104690 A 19940615; AT E142809 T1 19960915; DE 59108160 D1 19961017; DK 0456080 T3 19970217; DZ 1500 A1 20040913; ES 2094167 T3 19970116; GR 3021921 T3 19970331; MA 22148 A1 19911231; TN SN91034 A1 19921025

DOCDB simple family (application)

EP 91106956 A 19910429; AT 104690 A 19900511; AT 91106956 T 19910429; DE 59108160 T 19910429; DK 91106956 T 19910429; DZ 910056 A 19910508; ES 91106956 T 19910429; GR 960403325 T 19961205; MA 22418 A 19910506; TN SN91034 A 19910510