

Title (en)
Jack assembly.

Title (de)
Klinkensteckvorrichtung.

Title (fr)
Dispositif à jack.

Publication
EP 0462084 A2 19911218 (EN)

Application
EP 91850109 A 19910429

Priority
US 53696690 A 19900612

Abstract (en)

A switching coax jack is disclosed having a housing which contains first and second spaced apart electrical conductors. At least a first port is formed in the jack housing and sized to receive a jack plug which is inserted through the port and into the housing with a jack plug in electrical communication with the first conductor. A switch assembly contains a normal spring for connecting the first and second conductors. The spring is resiliently deformable away from electrical engagement with the first and second conductors. As the spring deforms, it assumes a deformed shape. The switch assembly includes a support surface opposing the normal spring and having a shape complimentary to the deformed shape of the normal spring. <IMAGE>

IPC 1-7
H01R 13/703; H01R 17/00

IPC 8 full level
H01R 13/703 (2006.01); **H01R 24/58** (2011.01)

CPC (source: EP KR)
H01R 13/70 (2013.01 - KR); **H01R 13/7032** (2013.01 - EP); **H01R 24/58** (2013.01 - EP); **H01R 2103/00** (2013.01 - EP);
H01R 2201/16 (2013.01 - EP)

Cited by
EP0788194A3; EP0708500A1; FR2725841A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0462084 A2 19911218; EP 0462084 A3 19920226; AU 646856 B2 19940310; AU 7500991 A 19911219; CA 2040398 A1 19911213;
IL 97886 A 19940624; JP H04248282 A 19920903; KR 920001783 A 19920130; NZ 238471 A 19930428

DOCDB simple family (application)
EP 91850109 A 19910429; AU 7500991 A 19910416; CA 2040398 A 19910415; IL 9788691 A 19910417; JP 16755091 A 19910612;
KR 910006830 A 19910427; NZ 23847191 A 19910610