

Title (en)  
OUTLET FITTING

Publication  
**EP 0464063 B1 19930210 (DE)**

Application  
**EP 90904751 A 19900313**

Priority  
DE 3909651 A 19890323

Abstract (en)  
[origin: WO9011414A1] An outlet fitting for sinks, wash-stands, bath-stands, bath-tubs and similar sanitary appliances comprises an outlet cup supported in a outlet hole. The closure element for the outlet hole is a plunger consisting of a guide element and a plunger head which can be moved longitudinally by means of a plunger rod. The upper rim region of the outlet cup forms a sealing collar for the plunger head in its closed position. To facilitate cleaning and improve the appearance of the sanitary appliance, the upper rim region (14) of the outlet cup (12), which forms a seat (13), is inserted into the wall of the appliance (10) in the outlet hole (11) to a depth such that the surface of the plunger head (15) in its open position is coplanar with the upper rim of the outlet hole (11). To mask the upper rim region (14) of the outlet cup (12) located inside the outlet hole (11), the diameter of the plunger head (15) is at least equal to the largest diameter of the upper rim region (14) of the outlet cup (12).

IPC 1-7  
**E03C 1/23**

IPC 8 full level  
**E03C 1/23** (2006.01)

CPC (source: EP)  
**E03C 1/23** (2013.01); **E03C 1/2302** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)  
**WO 9011414 A1 19901004**; AU 5284590 A 19901022; CN 1026716 C 19941123; CN 1046579 A 19901031; DD 293161 A5 19910822; DE 3909651 C1 19900906; DE 59000890 D1 19930325; EP 0464063 A1 19920108; EP 0464063 B1 19930210; ES 2040116 T3 19931001

DOCDB simple family (application)  
**DE 9000188 W 19900313**; AU 5284590 A 19900313; CN 90103602 A 19900323; DD 33902390 A 19900323; DE 3909651 A 19890323; DE 59000890 T 19900313; EP 90904751 A 19900313; ES 90904751 T 19900313