

Title (en)  
SPRAY HEAD FOR A SPRAY CAN

Publication  
**EP 0464122 B1 19921230 (EN)**

Application  
**EP 90905695 A 19900320**

Priority  
NL 8900729 A 19890323

Abstract (en)  
[origin: WO9011237A1] A spray head for a spray can, comprising a hollow stem having a bore which is adapted to be brought into communication with the liquid space of the spray can, and which on the other hand, terminates near a spray nozzle having an exit aperture, so as to force liquid driven into said bore by the outward pressure of the spray can through said aperture for being sprayed; according to the invention, in the flow path (3, 4, 6) of the liquid, a passage operating as a jet pump (7) driven by the liquid flow pressed outwards is included, the suction side (10) of which communicates with the ambient air.

IPC 1-7  
**B65D 83/28**

IPC 8 full level  
**B05B 7/04** (2006.01); **B05B 7/06** (2006.01); **B05B 7/10** (2006.01); **B65D 83/16** (2006.01); **B65D 83/28** (2006.01); **B65D 83/42** (2006.01); **B65D 83/58** (2006.01)

CPC (source: EP)  
**B05B 7/0425** (2013.01); **B05B 7/063** (2013.01); **B05B 7/10** (2013.01); **B65D 83/20** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE DK ES FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**WO 9011237 A1 19901004**; AU 5351690 A 19901022; EP 0464122 A1 19920108; EP 0464122 B1 19921230; JP H04504244 A 19920730; NL 8900729 A 19901016

DOCDB simple family (application)  
**NL 9000035 W 19900320**; AU 5351690 A 19900320; EP 90905695 A 19900320; JP 50537090 A 19900320; NL 8900729 A 19890323