

Title (en)
PRINTER WITH SHEET CASSETTE.

Title (de)
DRUCKER MIT EINER BLATTVORRATSKASSETTE.

Title (fr)
IMPRIMANTE AVEC UNE CASSETTE DE STOCKAGE DE FEUILLES.

Publication
EP 0466701 B1 19931020 (DE)

Application
EP 90902612 A 19900208

Priority
EP 89730094 A 19890405

Abstract (en)
[origin: WO9011893A1] Printers exist with a sheet supply cassette and a sheet separation device for the supply and separation of individual sheets before printing plus a tray designed to hold the individual sheets after printing. In order to give a compact printer design with respect to the space required by the sheet supply cassette (2), the cassette of the invention is made up of two elements (5 and 6) which can be rotated relative to each other. The first cassette element (5) is fixed inside the printer facing the sheet separation device (11) and the second cassette element (6) is designed as a pivoting cover (2) which is hinged to the printer and which, when closed, forms the top of the printer and, when open, is flush with the first cassette element (5) to form the sheet supply cassette (4).

IPC 1-7
B41J 11/58

IPC 8 full level
B41J 13/00 (2006.01); **B41J 11/58** (2006.01); **B41J 13/10** (2006.01); **B65H 1/04** (2006.01); **B65H 1/26** (2006.01); **B65H 11/00** (2006.01); **B65H 13/00** (2006.01); **B65H 31/00** (2006.01)

CPC (source: EP US)
B41J 11/58 (2013.01 - EP US)

Citation (examination)
IBM TECHNICAL DISCLOSURE BULLETIN, vol. 24, no. 8, January 1982, New York US, page 4348, Mott W. E. & Shakib I. D.: "Cover section for paper opening of a printer"

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
WO 9011893 A1 19901018; DE 59003163 D1 19931125; EP 0466701 A1 19920122; EP 0466701 B1 19931020; JP 2719984 B2 19980225; JP H08505114 A 19960604; US 5213427 A 19930525

DOCDB simple family (application)
DE 9000084 W 19900208; DE 59003163 T 19900208; EP 90902612 A 19900208; JP 50254490 A 19900208; US 77225091 A 19911007