

Title (en)  
BRIDGING MEMBER FOR DOUBLY EARTHED SAFETY PLUG

Publication  
**EP 0468315 B1 19930505 (DE)**

Application  
**EP 91111647 A 19910712**

Priority  
DE 9011104 U 19900727

Abstract (en)  
[origin: EP0468315A1] For a bridging member for doubly earthed safety plugs, having two limbs projecting upwards on the sides for clipping into an earthing tongue surrounding the bridging member, which earthing tongue has an integrally formed contact tongue for plugging onto a complementary earthing pin of a socket, which socket sinks into a complementary retaining chamber of the bridging member when the earthing tongue is clipped onto the said bridging member, it is proposed that the retaining chamber (11) for the contact tongue (10) has a tab-like projecting reinforcement (13) on the wall (12) facing the centre of the bridging member (1). This avoids the wall of the retaining chamber breaking during extrusion-coating of the bridging member. <IMAGE>

IPC 1-7  
**H01R 13/502; H01R 13/648**

IPC 8 full level  
**H01R 13/46** (2006.01); **H01R 13/502** (2006.01); **H01R 13/504** (2006.01); **H01R 13/648** (2006.01)

CPC (source: EP)  
**H01R 13/655** (2013.01); **H01R 24/30** (2013.01); **H01R 2103/00** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE DK ES FR IT LI NL SE

DOCDB simple family (publication)  
**EP 0468315 A1 19920129; EP 0468315 B1 19930505**; AT E89103 T1 19930515; DE 59100100 D1 19930609; DE 9011104 U1 19900927

DOCDB simple family (application)  
**EP 91111647 A 19910712**; AT 91111647 T 19910712; DE 59100100 T 19910712; DE 9011104 U 19900727