

Title (en)
FRICTIONAL ROTARY CONTROL

Publication
EP 0470018 B1 19930929 (FR)

Application
EP 91420280 A 19910726

Priority
FR 9010222 A 19900731

Abstract (en)
[origin: EP0470018A1] Means of friction, in the form of an elastic spring clip (3), are interposed between two rotatable elements, such as a disc (6) which is integral with a control axis and a wheel (2). The spring clip (3) has a part immobilised in rotation on one of the elements (6). This spring clip (3) is applied internally against a peripheral edge (7) of the wheel (2) constituting the other element. Application to devices with wheels, such as timers and programmers. <IMAGE>

IPC 1-7
G04B 11/00; **G05G 1/12**; **H01H 3/58**

IPC 8 full level
G04B 11/00 (2006.01); **G05G 1/12** (2006.01); **H01H 3/58** (2006.01); **H01H 43/10** (2006.01)

CPC (source: EP)
G04B 11/00 (2013.01); **G05G 1/12** (2013.01); **H01H 3/58** (2013.01); **H01H 43/10** (2013.01)

Citation (examination)
DE 1255746 B 19671207 - TELEFUNKEN PATENT

Cited by
EP0686897A1; CN102339086A; EP2085832A1; CH686470GA3; US5541895A; US2022197218A1

Designated contracting state (EPC)
DE ES FR IT

DOCDB simple family (publication)
EP 0470018 A1 19920205; **EP 0470018 B1 19930929**; DE 69100435 D1 19931104; ES 2046030 T3 19940116; FR 2665549 A1 19920207; FR 2665549 B1 19921204

DOCDB simple family (application)
EP 91420280 A 19910726; DE 69100435 T 19910726; ES 91420280 T 19910726; FR 9010222 A 19900731